



Effective Date: 28 July 2005

Revision Date: N/A

Revision: 000

## **ROTO-BRITE® L-555 TECHNICAL DATA SHEET**

---

### **ACID BURNISHING COMPOUND**

#### **APPLICATION:**

ROTO-BRITE® L-555 is a medium to high foaming, liquid burnishing compound designed to clean and burnish zinc, steel, copper, brass and aluminum as well as precious metals. Recommended usage rate is one ounce per gallon of water.

#### **CHARACTERISTICS:**

- Excellent burnishing for a wide variety of metals
- Will inhibit steel media during process
- Medium foam level
- Completely biodegradable

#### **PROPERTIES:**

- Slightly viscous green liquid, bland odor
- Density = 1.040 g/cc; 8.7 pounds/gallon
- Concentrate pH = 4.0; pH at 1% = 5.1
- Formulated without nitrites, phosphates or chromates
- Does not contain silicone, silicates, or silicon in any form

#### **FIRST AID:**

Should contact occur, flush area with plenty of water. For eyes, flush with water and seek medical attention promptly.

#### **CAUTION:**

ROTO-BRITE® L-555 is an industrial-grade product. Avoid excessive contact with skin, eyes, or clothing.

The data presented are believed accurate. Roto-Finish Company, Inc. can guarantee only its product. User must verify suitability to his own application.

KJE/jh 04/07/05



1600 Douglas Avenue • Kalamazoo, MI 49007  
(269) 345-7151 • FAX (269) 345-1710  
[SALES@ROTO-FINISH.COM](mailto:SALES@ROTO-FINISH.COM) • [WWW.ROTO-FINISH.COM](http://WWW.ROTO-FINISH.COM)

