

Hammond **ROTO
FINISH**

S I N C E 1 8 8 1

GEMINI[®]

For your Vibratory Finishing Needs.



MADE IN KALAMAZOO, MICHIGAN • USA

GEMINI®

Vibratory Finishing Machine

- Robust action.
- 4.3, 7 and 12 cubic feet capacity.
- Suspended on heavy duty coil springs.
- Main building component of tub is tankhead structure.
- U-shaped process channel with textured sidewalls.
- 4 polyurethane pop-in drain sizes included.
- Parts separation system with a dam; hand lever operated gate.
- Flat bottom versions also available.
- Unique drive system with adjustable top/bottom eccentric weights.
- Belt-drive to main shaft.
- Manual grease lubrication.
- On/Off control switch and solution system comes standard.*



GEMINI-7

GEMINI-12

GEMINI-4



*STANDARD: Floor stand with On/Off switch and water driven compound system.

◀ **Optional Semi-Automatic Control Panel**

230/460/3/60, 115 volt control circuit, fused disconnect, motor overload protection, on/off vibratory control, water driven compound system, machine hour meter and digital process timer. Free standing, pedestal mounted. Single direction rotation. I.E.C. components.



GEMINI® SPECIFICATIONS:

Model	Working Capacity cu ft / l	Overall Diameter in / mm	Overall Height in / mm	Process Channel Width in / mm	Screen Deck Height in / mm	Center Column Diameter in / mm	Base Diameter in / mm	No. of Drains	Motor HP hp / kw	Shipping Weight lb / kg
Gemini 4	4.3 / 122	42.5 / 1,079	44 / 1,143	9.5 / 241	39 / 990	19.5 / 495	34 / 863	1	2 / 1.49	850 / 385
Gemini 7	7 / 198	48.5 / 1,239	48 / 1,219	12 / 305	42 / 1,066	20.75 / 527	36 / 914	1	3 / 2.3	1,521 / 690
Gemini 12	11 / 311	42.5 / 1,320	51 / 1,295	13.4 / 340	44.6 / 1,133	21.75 / 552	36 / 914	1	5 / 3.72	1,728 / 784