



Introducing the **HAMMOND ROTO-FINISH FLAT FINISHER FF-12-1s** machine. An industrial duty through feed finishing machine which can be used wet or dry. It is compliant with European standards and designed to the highest specification. Typical applications include deburring, commercial polishing and “graining” of materials.

- 5.5 Hp Drive Motor
- ½ Hp Conveyor Motor
- 12” x 75” Abrasive Belt
- Variable Speed Conveyor 5-25 FPM
- 34.5” Work Height
- 1500 SFPM
- 12” x 4” Contact Wheel

- Quick Action Belt Tensioning
- Grooved Contact Wheel
- Dust Collection Scoop
- Manual Height Adjustment
- Main Door Interlock
- Low Air Pressure Shut Off



- 240 / 460V 3 Phase
- 50 / 60 PSI Air Pressure
- 4” Maximum Component Height
- 5” Minimum Component Length

- Manual Belt Tracking
- Hold Down Rollers
- Large Capacity Fluid Tank with Pump
- Flexible Spray Bar
- In Line Filter System

Size and Weight

Machine Weight: 815 lbs

Machine Dimensions (W x D x H): 37” x 33” x 75”



1600 Douglas Avenue
voice: (269) 345-7151
www.hammondroto.com

Kalamazoo, MI 49007
fax: (269) 345-1710
sales@hammondroto.com

