



Effective Date: 28 July 2005

Revision Date: N/A

Revision: 000

## **ROTO-CLEAN® RTC-190 TECHNICAL DATA SHEET**

---

### **FERROUS CORROSION INHIBITOR FOR SPRAY WASH APPLICATIONS**

#### **APPLICATION:**

ROTO-CLEAN® RTC-190 is a ferrous metal corrosion inhibitor specifically for spray wash systems. It is designed to protect tanks and cabinetry, of the spray wash system, as well as ferrous parts. Normal application is 3-20% by volume.

#### **CHARACTERISTICS:**

- Excellent wetting to provide uniform coverage
- Provides long term corrosion protection (1 week to 3 months) dependent on storage
- Extremely low foam
- Maintains bright surfaces
- Multi metal protection for composite parts

#### **PROPERTIES:**

- Operating temperature 150-180 F
- Reactivity: pH of concentrate 9.5; pH of 1% solution 8.5
- Specific gravity 1.03

#### **FIRST AID:**

Should contact occur, flush area with plenty of water. For eyes, flush with water and seek medical attention immediately.

#### **CAUTION:**

ROTO-CLEAN® RTC-190 is a concentrated, industrial-grade product. Avoid excessive contact with skin, eyes or clothing.

The data presented are believed accurate. Roto-Finish Company, Inc. can guarantee only its product. User must verify suitability to his own application.

KJE:dd 1/11/05



1600 Douglas Avenue • Kalamazoo, MI 49007  
(269) 345-7151 • FAX (269) 345-1710  
[SALES@ROTO-FINISH.COM](mailto:SALES@ROTO-FINISH.COM) • [WWW.ROTO-FINISH.COM](http://WWW.ROTO-FINISH.COM)

